

Fastmark M4 Series

Full 4" Print Width That Offers
Bluetooth and WiFi Simultaneously

Fastmark M4 – Powerful portable printer that can withstand up to 5 ft drops.

The Fastmark M4 is a rugged mobile printer ready to handle a wide variety of applications, from Healthcare to Warehousing, from receipts to barcode labels. Ready for use with PAL Plus, ZPL, Droid APP & SDK, WinCE Quick-link tool & SDK, and iOS SDK.

Standard Features

- PAL Plus and TSPL-EZ (EPL and ZPL emulations)
- Full 4" width media
- USB, Bluetooth, WIFI interfaces, optional RS-232
- 203 dpi printhead resolution
- Print speeds up to 4 ips
- Easy media loading
- Optional vehicle power adapter
- Belt clip and shoulder strap options
- Direct thermal printing on all popular media material
- 2 year warranty



All M4s are ready for loading custom PAL applications



PRINTER SPECIFICATIONS INCLUDE:

Printer Model	Fastmark M4	Interfaces	Standard: USB and Bluetooth Optional: 802.11 b/g/n WiFi
Resolution	203 dpi	Linear Bar Codes	Code 39, Code 93, Code128UCC, Code 128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, ITF14 TELPEN, PLANET, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS
Command Set	PAL Plus and TSPL-EZ (EPL and ZPL emulations)	2D Bar Codes	PDF-417, Micro PDF417, Maxicode, Data Matrix, QR Code, Aztec, Code 49, CODABLOCK F mode, GSI Databar
Printing Method	Direct Thermal	Windows compatibility	Win CE, NET, Pocket PC, Windows Mobile2002/2003SE, Windows 2000/XP/Vista/Win 7
Print Speed	Up to 4 ips	Battery	Rechargeable 7.2V DC 5800 mAh Li-on battery
Max Print Width	4.09 inches	Standard items	Belt clip, AC adapter, single battery charger, cleaning pen, sample receipt roll, Quick Guide
Max Print Length	90 inches	Options	Shoulder strap, IP54-rated protective case, Spare Battery, 4 bay Battery charger, Vehicle power adapter, linerless kit
Media width	2.0" – 4.4"	Power	Input: AC 100-240V, 50 – 60Hz 12 VDC 1.25 A output
Media Core diameter	.5" to 1"	Environment Conditions	Operation: 14 – 122 F, 10 – 90% non-condensing Storage: -40 – 140 F, 10 – 90% non-condensing
Label Roll Capacity	2.65" OD	Warranty	Two years
Media Types	Labels, receipt paper, continuous, die-cut, tag, notch, black mark, fan-fold, linerless	Agency Approval	CE Class B, FCC, CB, CCC, TUV, SRRC
Sensors	Gap, black mark reflective, head open, peel		
Enclosure	Plastic with rubber over-mold construction 2 buttons (Power and Feed) 6 LED's for battery status Optional LCD model: 4 buttons(Power, Feed, Menu, Info), 2 LED's and 2" LCD display with backlight Clamshell design with Belt clip or shoulder strap		
Physical Dimension	3.11" (D) x 6.30" (W) x 7.54" (H) Weight 2.4 lbs with battery		
Real time clock	Standard		
Processor	32-bit RISC CPU		
Memory	16MB Flash 32MB SDRAM microSD card reader for Flash expansion up to 4 GB		

AMTDatasouth

Corporate Headquarters
803 Camarillo Springs Road, Suite D,
Camarillo, California 93012
(805) 388-5799 PH
(805) 484-5282 FX

www.amtdatasouth.com

Charlotte Operation
5033 Sirona Drive, Suite 800
Charlotte, NC 28273
(704) 523-8500 PH
(704) 525-6104 FX

Part No. 120436 rev. A
Specifications are subject to change without notice.
#16488

