

NEW

KPSL/KPST

54 - 58 - 60 mm



Key features

- Very compact design
- Easy to integrate
- High speed printing



Characteristics	Unit	KPSL	KPST
Printing Speed (max)	mm/s	150 (12V) - 250 (24V)	100 (12V) - 150 (24V)
Printing Width	mm	56	52
Resolution	dot/mm	8	
Number of Dots	dot	448	
Number of Columns	column	28 or 37 max	
Character Size	dot*dot	12 x 24 or 16 x 24	
Resident Code Page	---	CP 437, 737, 850, 852, 858, 860, 862, 863, 865, 866, 1252, 1256 + EasyFont Compatible	
Bar Code Type	---	Code 39, 93, 128, Interleaved 2/5, UPC-A, UPC-E, JAN8 (EAN8) & JAN13 (EAN13), Codabar, PDF417	
Paper Width	mm	58 - 60	54
Paper Roll Diameter	mm	up to 200	
Paper Thickness	µm	From 60 to 100	From 60 to 185
Paper Loading	---	Auto loading	
Operating Voltage	VDC	12 or 24V	
Power Consumption	W	75	
Head Pulse Life	pulse	1*10 ⁸	
Mechanical Reliability	Km	100	
Dimensions (W*D*H)	mm	95 x 93 x 118	
Weight	g	960	
Operating Temperature	°C/F	- 25 to + 70 / -13 to + 158	
Operating Humidity	% RH	20 to 85 (non condensing)	
Cutter	---	Guillotine (full and partial cuts)	
Cutter Life	cuts	1 Million	500 thousands
Data Buffer	Kbytes	4	
Interface	---	RS232 or USB 2.0	
Driver	---	Windows™ 00 / XP / Vista / Linux	
CEM & Safety Standards	---	UL60950-1, CSA 22.2-60950-1, IEC60950, CE Class B, FCC Class B, C-Tick	
Sensors	---	Top of form and paper out	
Accessories	---	Power supply	

