

## PRODUCT SPECIFICATIONS

# E-CLASS



▪ E-4203    ▪ E-4204    ▪ E-4304

The Datamax E-Class family is a lightweight, space-saving line of thermal printers designed with leading edge technology for a multitude of label and tag printing applications.

These printers are engineered for small size but packed with big features including an advanced 32-bit multi-tasking processor with two megabytes of memory, serial, parallel, and USB communication interfaces, and a three-button control panel. In addition, a full complement of industry standard linear bar codes as well as the complex two-dimensional symbologies such as MicroPDF417, Datamatrix, Maxicode, Aztec, and TLC39 are resident in the printer's memory.

With all this power loaded into such a small footprint, the E-Class family is the printer choice for a wide variety of low to medium volume labeling applications ranging from the needs of those in an office or research facility to those of a shipping or transportation center. And depending upon the model you choose, a four-inch per second print speed, a 300 dot per inch print resolution, plus the ability to accommodate a five inch roll of media can provide added versatility for all of your applications.

All E-Class printers share an assortment of options including a cutter, a label present sensor, and an assortment of international character font sets. Also, connectivity is never an issue because the E-Class printer can be easily networked with the Datamax DMX-100 Ethernet print server.

When it comes to big performance in a small package, there is just one choice - the E-Class family of printers. They are the most affordable entry-level printing solution available in the marketplace today.

### E-CLASS PRINTERS

are ideal for applications such as:

- Admissions
- Product Labeling
- Patient File Tracking
- Postal Services
- Drivers Licenses
- Small Business
- Automobile Registration

# DATAMAX®

[www.datamaxcorp.com](http://www.datamaxcorp.com)



#### CORPORATE HEADQUARTERS

4501 Parkway Commerce Blvd.  
Orlando, Florida USA 32808  
Phone (407) 578-8007  
Fax (407) 578-8377  
[customercare@datamaxcorp.com](mailto:customercare@datamaxcorp.com)

#### DATAMAX LABELS AND RIBBONS

Phone (800) 321-2233  
Fax (800) 436-8920  
[dmxmedia@datamaxcorp.com](mailto:dmxmedia@datamaxcorp.com)

#### DATAMAX LATIN AMERICA

Phone (407) 523-5520  
Fax (407) 578-8377  
[tdelgado@datamaxcorp.com](mailto:tdelgado@datamaxcorp.com)

#### DATAMAX INTERNATIONAL

Phone +44 1279 772200  
Fax +44 1279 424448  
[rbyrne@datamaxcorp.com](mailto:rbyrne@datamaxcorp.com)

#### DATAMAX ASIA-PACIFIC REPRESENTATIVE OFFICE

Phone +65-542-2611  
Fax +65-542-3611  
[datamax@pacific.net.sg](mailto:datamax@pacific.net.sg)

#### DATAMAX CHINA REPRESENTATIVE OFFICE

Phone +86 21 64952882  
[datamax\\_cn@china.com](mailto:datamax_cn@china.com)

## PRODUCT SPECIFICATIONS

# E-CLASS

	E-4203	E-4204	E-4304
PRINT SPEED	3 IPS	4 IPS	4 IPS
RESOLUTION	203 DPI	203 DPI	300 DPI
SUPPLY ROLL CAPACITY	4" (101.6 mm)	5" (127.0 mm)	5" (127.0 mm)

PRINTER TYPE	Direct Thermal, Optional Thermal Transfer
BAR CODE MODULUS	5 mil to 55 mil (203 dpi) / 3.3 mil to 40 mil (300 dpi) "X" dimension in picket fence or ladder orientations
MEDIA WIDTH	1" – 4.3" (25.4mm – 109.2mm)
MEDIA TYPE	Roll-fed or fan-fold materials, die-cut or continuous labels; perforated or continuous tag/ticket stock
PRINT LENGTH	.375" – 24" (9.5mm – 609.6mm)
MEDIA THICKNESS	.0025" – .0100" (.0635mm – .254mm)
MEDIA SENSING	"See through" for liner backed die cut labels and tags. Left bias reflective sensor for black mark label media
LABEL BACKFEED	For use with optional cutter
RIBBONS	Industry standard ribbon widths; 0.5" (13mm) ribbon core, 361' (110M) in length
CABINET	Plastic construction, clear top window to easily monitor media supply levels
BAR CODES	Code 3 of 9, UPC-A, UPC-E, Interleaved 2 of 5, Code 128, EAN-8, EAN-13, HIBC, Codabar, Plessey, UPC 2 and 5 digit addendums, Code 93, Postnet, UCC/EAN Code 128, Telepen, UPS MaxiCode, FIM, PDF417, USD-8, Datamatrix, QR Code, Aztec, TLC 39, Micro PDF417
RESIDENT FONTS	Ten alphanumeric fonts from .08" (2mm) to .25" (6mm) including OCR-A, OCR-B, CG Triumvirate™ smooth font from AGFA®.
DOWNLOADABLE FONT TYPES	True-Type, AGFA® Intellifont™, Bitmap
CHARACTER SET	Modified IBM® Code Page 850; includes characters for English and most European, Scandinavian and Spanish speaking countries. Scalable fonts can be used with over 50 resident character sets.
FONT EXPANSION/ROTATION	All fonts expandable vertically and horizontally up to 24x; fonts and graphics can be printed in four directions: 0°, 90°, 180° and 270°
GRAPHICS SUPPORTED	.PCX, .BMP and .IMG files
REVERSE FIELDS/MIRROR IMAGE	Any font or graphic field can be printed as a normal or reverse image
MEMORY	2MB DRAM; 1MB Flash
INTERFACES	USB, Centronics® Parallel port, RS232 at 600 to 38,400 BPS
WINDOWS® DRIVER	Used for creating label formats using virtually any Windows®-based program. Included on Datamax Accessories CD, or via our web site at <a href="http://www.datamaxcorp.com">www.datamaxcorp.com</a>
POWER SOURCE	External power supply; specify appropriate power supply and cord when ordering
OPERATING TEMPERATURE	40°F to 95°F (4°C to 35°C)
DIMENSIONS	7.05" H x 8.77" W x 10" D (179mm H x 223mm W x 254mm D)
WEIGHT	Printer: 5.2 lbs. (2.4kg)

### DATAMAX E-CLASS OPTIONS:

- THERMAL TRANSFER
- LABEL PRESENT SENSOR
- 4 MB FLASH (MAIN BOARD)
- LIGHT DUTY CUTTER
- EXTERNAL MEDIA SUPPLY STAND
- ILPC
- STANDARD CUTTER
- RESIDENT SCALABLE FONTS
- DMX100 ETHERNET PRINT SERVER
- ADJUSTABLE MEDIA SENSOR

Built to UL, Canadian, and European safety standards, FCC Class A emissions standard and CE Mark. This data sheet is for informational purposes only. DATAMAX MAKES NO WARRANTIES, EXPRESSED OR IMPLIED IN THIS SUMMARY. Specifications are subject to change without notice. All trademarks are the property of their respective owners. ©2004 DATAMAX BAR CODE PRODUCTS CORPORATION. All rights reserved. Datamax is an ISO 9001 registered company.

Rev. 03/04

**DATAMAX®**

www.datamaxcorp.com



## About BarcodesInc

### Who We Are

BarcodesInc is North America's leading provider of... [The following text is heavily garbled and appears to be a placeholder or corrupted content.]

### We Owe Our Success To You

Our success is due to the support of our customers... [The following text is heavily garbled and appears to be a placeholder or corrupted content.]

## Why Choose BarcodesInc?

### Dedicated Account A UbU Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

### Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

### Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

### Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same day.

### Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

### Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service team.

### Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

## BRANDS



AND MORE