

Reliable, easy to use, thermal label printers designed to optimize supply chain management



IBM 4400 Thermal Printers



Highlights

- ***High-quality, high performance thermal printing in 4-, 6- and 8-inch widths at up to 10 inches per second***
- ***Rugged die-cast aluminum base for tough industrial environments***
- ***Optional IPDS enables dynamic document composition and enhanced print reliability***
- ***Optional bar code validator***
- ***Powerful remote management***

Supply chain efficiency is required in today's industrial environments, where reliable output management is critical. IBM® 4400 Thermal Printers offer ease of use, flexible media handling, and powerful remote management to keep your information flowing.

Reliability

Exceptional print quality and performance are inherent to the printer's thermal print head control technology. In addition, the optional bar code validator features "read-after-print" technology to help ensure bar code validity and scannability.

Two direct-drive motors control the ribbon spindles and are designed to sustain ribbon tension throughout the life of the printer, minimizing torn ribbons and downtime.

Ease of use

The IBM 4400 simplifies forms loading and supplies replacement with easy access to internal components. The user-friendly front panel controls and backlit display make it easy to set up and store customized printer configurations. An optional cutter and tray allow labels to be cut and collected as they are printed, providing additional flexibility.

Remote management

Using the Printer Management Utility and the IBM 4400 internal Ethernet option, multiple printers can be easily managed and configured with a user-friendly interface.

IBM service and supplies

IBM offers a full range of service to meet your needs, available 24 hours a day, 7 days a week. Service calls can be initiated via the internet through Service Direct at ibm.com/printers, or by calling 1-800-358-666.1

IBM 4400 thermal Label Printer supplies are designed to enhance printing capabilities and to help prevent premature printhead wear.



IBM Printer Outlet.com
1-866-430-6202

IBM 4400 Printers at a glance

For expanded specifications visit: ibm.com/printers/4400

Print Speed and Resolution (inches per second)	Models 004/006	Model 008
	10 ips @ 203 dpi (254 mm/sec) 8 ips @ 300 dpi (203 mm.sec)	8 ipd @ 203 dpi (203 mm/sec) 6 ips @ 300 dpi (152 mm/sec)
Memory	Flash: 4 MB/10 MB max.	DRAM: 8 MB/16 MB max.
Printing Methods	Thermal transfer or direct thermal	
Printable Width	Model 004: 4.1" maximum (104 mm) Model 006: 6.6" maximum (168 mm) Model 008: 8.5" maximum (216 mm)	
Media Handling	Manual tear-off mode, Optional peel-off mode labels peel and present and rewind mode Optional cutter and tray for unattended operation	

Media Compatibility

Media types:	Roll or fanfold; die-cut or continuous; labels, tags, and tickets; paper, film or synthetic stock; thermal transfer or direct thermal
Media width:	Model 004: 0.75" to 4.5" (19 to 114 mm) Model 006: 2.0" to 6.8" (51 to 171 mm) Model 008: 3.0" to 8.75" (76 to 222 mm)
Media thickness:	0.0025" to 0.010" (0.07 to 0.25 mm)
Roll core diameter:	3.0" (76 cm)
Maximum roll diameter:	8.0" (209 cm)
Thermal transfer ribbons:	Standard ribbon length: 2,050 feet (625 m)

Datastream Support

ASCII, Code V and IGP Optional: IPDS, SCS

Bar Codes

Code 39, Code 128 (A,B,C), Codabar, Interleaved 2 of 5, FIM UPC-A, UPC-E, UPC-EO, EAN 8, EAN 13, Code 93, Postnet, Postbar UCC/EAN 128, PDF 417, UPS Maxicode, Royal Mail

Interface Drivers

Standard interfaces:	RS-232/RS-422 (DB 25 pin)/EEE 1284 (Centronics)
Optional interfaces:	Coax/Twinax, 10/100BaseT Ethernet
Windows drivers:	Microsoft® Windows® 95/98, Windows 2000 and Windows NT®

Power Requirements

Consumption:	Max. Typical; 115/240 VAC 80/160 150 Watts PowerFactor Correction
Regulatory compliance:	FCC, UL, CSA, TUV, Energy Star® mode (under 45 watts)

Physical Characteristics

	Depth	Height	Width	Weight				
Model 004:	17"	(43.1 cm)	12"	(30.5 cm)	10"	(25.4 cm)	35 lbs.	(15.9 kg)
Model 006:	21"	(53.5 cm)	12.75"	(32.4 cm)	13.25"	(33.7 cm)	43 lbs.	(19.5 kg)
Model 008:	21"	(53.5 cm)	12.75"	(32.4 cm)	15.25"	(38.7 cm)	45 lbs.	(20.4 kg)

For more information on the implications of the euro, visit the IBM euro Web site at ibm.com/euro

Microsoft and Windows are registered trademarks of Microsoft Corporation.

ENERGY STAR is a U.S. registered mark. The Energy Star Emblem does not represent EPA endorsement of any product or service.

Other company, product and service names may be trademarks or service marks of others.



IBM Printer Outlet.Com
1-866-430-6202

Fax for a Quick Quote
817-430-6250

#4400

Organization _____

Name _____

Phone _____ **Fax number** _____
(area code) (area code)

E-mail _____

Address _____

City _____ **State** _____ **Zip** _____

Please indicate your specifications or requirements:

Additional comments:

