

7106



Tally Dascom's 7106 direct thermal printer offers reliability, precision and performance in desktop size, where space is limited.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media loading. The clear panel enable simple and effective operation making it very simple to use.

The mechanism uses an all-metal construction ensuring reliable operation, a must for all industrial environments.

Highlights at a glance:

- Space-Saving Design Concept
- Easy and Quick media loading
- Serial and USB Standard
- Supports Zebra® and Datamax® emulation
- Optional Cutter and Peeler
- Internal 5 inch (125mm) media capacity

The 7106 offers a wide range of features and options usually only found on high performance machines.

For example, it has an internal power supply providing the most reliable operation and avoiding problems usually associated with external power supplies.

The 7106 is easily integrated into existing systems, internal Ethernet interface is also available. In addition to this, the 7106 is also available with options such as a cutter and a peeler to meet industry requirements.

Configurations:

- **7106** Standard Product

7106

Print Speed	6 ips (152 mm/sec)
Print Width	4.10 inches (104.1 mm)
Print Method	Direct Transfer
Print Length	0.25" to 32" (6.35 mm to 812,8 mm)
Resolution	203 dpi:
Font Bitmapped	7 styles, True Type
Printhead Life	50 km or 6 months
Memory	16 Mb SDRAM; 4 Mb Flash
Connectivity Standard	Serial (RS-232C), USB (Version 1.1)
Connectivity Optional	Ethernet LAN (10/100 BaseT), Parallel (IEEE-1284)
Emulation	Auto-switching Zebra ZPL-II and Datamax I-Class, DMX400, Prodigy Plus
Consumables	Thermal direct paper and label
Media Width	0.77" to 4.65" (19.6 mm to 118.1 mm)
Media Length	0.25" to 32" (6.35 mm to 812,8 mm)
Roll Diameter	Internally: 5" (127 mm) . Externally 8" (203 mm) with optional holder Core size 1" - 3" (25 mm to 76 mm).
Indexing	Fully adjustable rear sensor
Barcodes	Code11, Code39, Code93, Code128, I2of5, S2of5, EAN8, EAN13, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC A/E, POSTNET, Planet, Code49, PDF417, CODABLOCK, Maxicode, DataMatrix, QR Code, RSS, TLC39
Physical Weight	3.6 kg
Physical Size	183 x 231 x 289 mm (H x W x D)
Power Voltage	220-240 V AC, 50-60Hz
Power Consumption	max 12,9W in Standby, 196W in Operating
Drivers	Windows XP, 2003, Vista, Win 7/8 (32/64 Bit)
Temperature	+5°C to +35°C
Humidity	30% to 80% (not condensing)
Acoustic (ISO 7779)	<55 dB(A)
Options	Auto Cutter, Peeler, Parallel and LAN Interfaces
Note	Accessories Supplied: Head cleaning pen, Start-Up Guide, CD including: Manuals, Drivers and EasyConfig Too

DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 355130 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 