

## 7206



The TallyDascom 7206 thermal transfer models offer industrial performance in desktop size. The mechanism uses an all-metal construction ensuring reliable operation, a must for all industrial environments.

The user friendly design of the printers allows a space saving vertical opening and an easy to use print mechanism ensures quick and easy loading of labels and ribbons. An intelligent ribbon control system stops the ribbon from wrinkling, giving you constant height print quality.

### Highlights at a glance:

- Space-Saving Design Concept
- Easy and Quick media loading
- Serial and USB Standard
- Supports Zebra® and Datamax® emulation
- Optional Cutter and Peeler
- Internal 5 inch (125mm) media capacity

The 7206 offers a wide range of features and options usually only found on high performance machines. The 7206 is easily integrated into existing systems, internal Ethernet interface is also available.

In addition to this, the 7206 is also available with options such as a cutter and a peeler to meet industry requirements.

The 7206-300 with a resolution of 300 dpi is ideal for printing labels with logos, images and graphics.

### Configurations:

- **7206** Standard Product
- **7206-300** Standard Product with 300 dpi resolution

## 7206

<b>Print Speed</b>	6 ips (152 mm/sec)
<b>Print Width</b>	4.10 inches (104.1 mm)
<b>Print Method</b>	Direct or Thermal Transfer
<b>Print Length</b>	0.25" to 32" (6.35 mm to 812,8 mm)
<b>Resolution</b>	203 dpi / 300 dpi
<b>Font Bitmapped</b>	7 styles, True Type
<b>Printhead Life</b>	50 km or 6 months
<b>Memory</b>	16 Mb SDRAM; 4 Mb Flash
<b>Connectivity Standard</b>	Serial (RS-232C), USB (Version 1.1)
<b>Connectivity Optional</b>	Ethernet LAN (10/100 BaseT), Parallel (IEEE-1284)
<b>Emulation</b>	Auto-switching Zebra ZPL-II and Datamax I-Class, DMX400, Prodigy Plus
<b>Consumables</b>	Ribbon, thermal transfer paper/labels, direct thermal paper/labels
<b>Media Width</b>	0.77" to 4.65" (19.6 mm to 118.1 mm)
<b>Media Length</b>	0.25" to 32" (6.35 mm to 812,8 mm)
<b>Roll Diameter</b>	Internally: 5" (127 mm) . Externally 8" (203 mm) with optional holder Core size 1" - 3" (25 mm to 76 mm).
<b>Indexing</b>	Fully adjustable rear sensor
<b>Ribbon Type</b>	Wax, Wax/Resin or Resin
<b>Ribbon Length</b>	max. 360 m
<b>Barcodes</b>	Code11, Code39, Code93, Code128, I2of5, S2of5, EAN8, EAN13, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC A/E, POSTNET, Planet, Code49, PDF417, CODABLOCK, Maxicode, DataMatrix, QR Code, RSS, TLC39
<b>Physical Weight</b>	4.9 kg
<b>Physical Size</b>	263 x 231 x 289 mm (H x W x D)
<b>Power Voltage</b>	220-240 V AC, 50-60Hz
<b>Power Consumption</b>	max 13 W in Standby, 156 W in Operating
<b>Drivers</b>	Windows XP, 2003, Vista, Win 7/8 (32/64 Bit)
<b>Temperature</b>	+5°C to +35°C
<b>Humidity</b>	30% to 80% (not condensing)
<b>Acoustic (ISO 7779)</b>	<55 dB(A)
<b>Options</b>	Auto Cutter, Peeler, Parallel and LAN Interfaces
<b>Note</b>	Accessories Supplied: Head cleaning pen, Start-Up Guide, CD including: Manuals, Drivers and EasyConfig Too

### DASCOM GB Limited

Hart House, Priestley Road  
Basingstoke, Hampshire RG24 9PU  
Tel: +44 1256 355130 – Fax: +44 1256 481400  
info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 