

DL-310 Thermal Label Printer



Tally
DASCOM

Tally Dascom's DL-310 thermal transfer printer offers reliability, precision and performance in desktop size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media and ribbon loading. The clear panel enable simple and effective operation making it very simple to use.

Highlights at a glance:

- 300 DPI high quality printing
- Easy ribbon and paper loading
- Supports a wide variety of interfaces
- Supports ZPL, EPL and TSC emulations
- Optional cutter, peeler
- 300 m ribbon and 5 inch paper capacity

The DL-310 is easily integrated into existing systems as it supports a wide variety of optional interfaces. In addition, the DL-310 is also available with an optional cutter or peeler to meet the various industry requirements.

Configurations:

- Standard Product (USB only)
- Printer with Parallel / Serial / Ethernet / WIFI / Bluetooth interface option
- Printer with cutter option
- Printer with peeler option

DL-310

Print Speed	4 ips (102 mm/sec)
Print Width	4"/ 106 mm
Print Method	Direct Thermal or Thermal Transfer
Print Head Lifetime	30 km or 6 months whichever is earlier
Resolution	300 dpi
Fonts	Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM
Memory	16 MB SDRAM; 8 MB Flash
Interface	USB (2.0 Full Speed)
Interface Options	Serial (RS-232C), Parallel (IEEE-1284), Ethernet, WIFI, Bluetooth
Emulations	ZPL, EPL, TSC
Ribbon	Width: 33 - 110 mm; Length: 300 m Core diameter: 25.4 mm; Outside diameter: 68 mm
Media	Width: 25 - 118 mm; Thickness: 0.06 - 0.18 mm Core diameter: 25.4 / 38.1 mm; Outside diameter: 127 mm
Media Type	Thermal paper, media, black mark paper
Sensors	Paper detection sensor; Black mark sensor, Label gap sensor, Ribbon sensor, Mechanical sensor Optional: paper taken sensor
Barcode	1D: Code 39, UPC-A, UPC-E, Matrix 25, Industrial 2 of 5, Interleaved 2 of 5, Post 2 of 5, Code 128, EAN-8, EAN-13, HBIC (Code 39), Codabar, UPC-2, UPC-5, Code 93 2D: PDF 417, MaxiCode, QR Code, Data MatrixR
Physical Weight	3 kg
Physical Size	176 x 230 x 290 mm (H x W x D)
Power Voltage	100-240 V AC, 50-60Hz
Printer Driver	Windows (32/64 Bit)
Temperature	Operating: 5° C - 40° C
Humidity	Operating: 20% - 95% (not-condensing)
Acoustic	< 55 dB(A)
Options	Cutter, Peeler

DASCOM AP Pte Ltd

21 Bukit Batok Crescent

#29-81 WCEGA Tower

Singapore 658065

Tel: +65 6760 8833 – Fax: +65 67601066

sales@dascom.com.sg – www.dascom.com.sg

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 