

B-SV4 Series



B-SV4 Series

Specifications

	- OV.	
Model	B-SV4D	B-SV4T
Technology	Direct Thermal	Thermal transfer / Direct Thermal
Printhead	Flat type	
Resolution	8 dots/mm (203 dpi)	
Print Width	Maximum 108 mm	
Print Length	Maximum 609.6 mm	Maximum 609.6 mm
Print Speed	up to 127 mm/sec (5 ips)	
Interfaces	Serial port, parallel port*, USB, LAN**	
Barcodes	Code 39, Code 39C, Code 93, Code 128 UCC, Code 128, Code 11, Codabar, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5), MSI, ITF, Plessey, Postnet, RSS	
2D Codes	Data Matrix, PDF 417, Maxicode, Micro PDF 417, QR code	
Fonts	Alpha bitmap font (6 fonts), Outline font (1 font)	
Models	Standard or Cutter	Standard
Options	Keyboard, extra cutter module for thick paper and partial cutting, expansion flash memory module, external media roll holder, strip sensor module, LAN adapter	
Dimensions (mm)	200(W) x 232(D) x 169(H)	213(W) x 314(D) x 188(H)
Weight	2 kg (without media and AC adapter)	2.8 kg (without media and AC adapter)

- * Standard on GS10 model
- ** Standard on GS12 model



The CD-ROM supplied with these printers includes the Owners manual in various languages, technical manuals (Programming, Supply, etc.) and Bartender TEC UltraLite labelling software.

Your TOSHIBA TEC dealer:

Customers' benefits

The B-SV4 series are packed with features designed to benefit

- high speed printing and throughput leading to increased efficiency and productivity
- time-saving and minimal training due to fast and easy
- reduced downtime and increased productivity as a result of high reliability
- reduced repair and recovery costs, and maximized Return On Investment during the total life cycle

TOSHIBA

TOSHIBA TEC CORPORATION RETAIL INFORMATION SYSTEMS COMPANY

Tel. +81 3 6422 7423 info-ris@toshibatec.co.jp

TOSHIBA TEC AUSTRALIA PTY. LTD.

Tel. +61 (0)2 88 45 62 00 sales@toshihatec.com.au www.toshibatec.com.au

TOSHIBA TEC EUROPE RETAIL INFORMATION SYSTEMS

www.toshibatec-eu.com

Tel. +32 (0)2 410 21 00

info@toshibatec-eu.com www.toshibatec-eu.com

Austria

Tel. +43 (0)1 319 72 11 marketing@toshibatec-eu.de www.toshibatec-eu.de

Tel. +32 (0)2 410 21 00 barcode@toshibatec-eu.be www.toshibatec-eu.be

Tel. +33 (0)1 58 07 20 00 info@toshibatec-eu.fr www.toshibatec-eu.fr

Tel. +49 (0)2 15 18 38 01 marketing@toshihatec-eu de www.toshibatec-eu.de

Tel. +353 (0)1 465 22 20 info@toshibatec-eu ie www.toshibatec-eu.co.uk

Portugal Tel. +351 (0)214 222 064

comercial@toshibatec-eu.pt www.toshibatec-eu.pt

Tel. +34 (0)91 502 15 90 marketing@toshibatec-eu.es www.toshibatec-eu.es

Tel. +44 (0)870 890 7200 marketing@toshibatec-eu.co.uk www.toshibatec-eu.co.uk

GROUP Companies

www.toshibatec.it

TEC Italia, S.r.l. Gruppo Toshiba Tel. +39 (0)2 48 60 24 61 info@toshibatec.it

TEC Polska Sp. z.o.o. Tel. +48 (0)22 501 67 70 info@toshibatec-eu.pl www.toshibatec-eu.pl



www.toshibatec-eu.com

The Toshiba B-SV4 series are 4" desktop printers that out perform all printers in their class, whilst being extremely competitively priced. Their innovative design and high quality build provides incredible reliability as well as fast and easy handling.

Value Desktop Printers u p e r

TOSHIBA

Leading Innovation >>>



The super value **B-SV4** series comes with a number of interfaces as standard. Their main features will be appreciated by a variety of industries including transport and logistics, retail, leisure (ticketing), healthcare and office.

Speed

With a print speed of 5" (127 mm) per second, high speed printing is one of the main features of the B-SV4 series. Fitted with a fast 32 bit RISC CPU for high throughput, it also has a large 2 MB DRAM image buffer to give a maximum print length of 609.6 mm (B-SV4D), 998.0 mm (B-SV4T), 2 MB Flash memory and up to 8 MB optional memory expansion for large data file storage.

Ease of use

Printhead, paper and sensor access is made simple by the 90° cover opening mechanism, ensuring easy media loading and cleaning. Additionally, a movable label sensor supports most media configurations.

▼ Easy ribbon loading



Reliability

The B-SV4 series have a robust doublewalled cover design that protects the inner mechanisms against dust and external damage. Tool-less replacement of the printhead and a clip-in platen adds up to simple trouble-free maintenance. In addition to their competitive price, the B-SV4 series are equipped with a high quality long-life thermal head (50 km life time) which contributes to a lower total cost of ownership.



Applications

B-SV4

- Transport and Logistics
- Express courier companies
- Transportation companies
- Airports / Airplane companies
- Railway organisations
- Logistics centres / Warehousing companies
- Post organisations
- Retail
- Hypermarkets / Supermarkets
- Department stores
- Specialised stores
- Hospitality
- Leisure (ticketing)
- Cinema / theatre
- Museum
- Entertainment parks
- Sport centres / competitions
- Healthcare
- Hospitals
- Laboratories
- Pharmaceuticals companies
- Office

Incredible Performance and Quality at a Budget Price!

Easy connectivity

The B-SV4 series comes with a wide variety of interfaces as standard:

- RS-232C (up to 56,000 bps)
- GS10 model: SPP parallel port (Centronics)
- USB v1.1 port for fast data transfer
- GS12 model: internal LAN.


An optional LAN adapter is available for the GS10 model.

Full compatibility

The B-SV4 series supports worldwide dot-matrix and TrueType fonts. It has an auto switching 100-240V external AC adapter. Using the Windows drivers or the inbuilt TOSHIBA TEC programming language (TPCL2 Lite) the B-SV4 series can work with formats designed for their industrial siblings.

Compact

The B-SV4 series are small (SV4D: 200 mm x 232 mm, SV4T: 213 mm x 314 mm) and light (SV4D: 2 kg, SV4T: 2.8 kg excluding media & AC adapter) printers which can be installed immediately in any convenient place.





▼ Clip-in platen

