

Specifications

Model	B-SX4	B-SX5
Technology	Thermal Transfer / direct thermal	
Printhead	Edge type	
Resolution	8 dots/mm (203 dpi)	12.05 dots/mm (306 dpi)
Print Width	Maximum 104 mm	Maximum 127,5 mm
Print Length	Maximum 1,498 mm	
Print Speed	up to 254 mm/sec (10 ips)	up to 203.2 mm/sec (8 ips)
Ribbon Save	Optional	Standard
Interfaces	2 serial ports, Bi-directional parallel port, Expansion I/0*,PCMCIA I/F**, 10/100 Internal LAN I/F**, USB**	
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Industrial 2 of 5, ITF, Postnet, RM4SCC, KIX-code, RSS14	
2D Codes	Data Matrix, PDF 417, Maxicode, QR code, Micro PDF 417	
Fonts	Bitmap font (21 fonts), Outline font (7 fonts), Writable characters (132 fonts), Optional TrueType fonts (20 types)**	
Optional	Swing cutter module, rotary cutter module, strip module & rewinder***, USB Interface, built-in LAN board, Expansion I/O***, 2-slot-PCMCIA I/F board, RFID kit	
Dimensions	291 mm (W) x 460 mm (D) x 308 mm (H)	
Weight	18 kg (without media and ribbon)	19 kg (without media and ribbon)

^{*} Option for the B-SX4, ** Optional, *** Standard on the B-SX5

Your TOSHIBA TEC dealer:

All company and/or product names are trademarks and/or registered trademarks of their respective owners. All features and specifications described in this brochure are subject to change without notice.

B-SX4 & B-SX5

Customers' benefits

The B-SX4/SX5 are packed with advantageous features for the user, including:

- high speed printing leading to increased efficiency and productivity
- time-saving and minimal training due to fast and easy handling
- reduced downtime and increased productivity as a result of high reliability
- minimal repair and recovery costs, and maximised ROI during total life cycle
- perfect readability of labels & barcodes due to built-in high quality print technology
- supplied with Bartender UltraLite labelling software



TOSHIBA

TOSHIBA TEC CORPORATION RETAIL INFORMATION SYSTEMS COMPANY

Tel. +81 3 6422 7423 info-ris@toshibatec.co.jp www.toshibatec-ris.com

TOSHIBA TEC AUSTRALIA PTY. LTD.

Tel. +61 (0)2 88 45 62 00 sales@toshibatec.com.au www.toshibatec.com.au

TOSHIBA TEC EUROPE RETAIL INFORMATION SYSTEMS

Tel. +32 (0)2 410 21 00 info@toshibatec-eu.com www.toshibatec-eu.com

Tel. +43 (0)1 319 72 11 marketing@toshibatec-eu.de www.toshibatec-eu.de

Tel. +32 (0)2 410 21 00 barcode@toshibatec-eu.be www.toshibatec-eu.be

France

Tel. +33 (0)1 58 07 20 00 info@toshibatec-eu.fr www.toshibatec-eu.fr

Tel. +49 (0)2 15 18 38 01 marketing@toshibatec-eu.de www.toshibatec-eu.de

Tel. +353 (0)1 465 22 20 info@toshibatec-eu.ie www.toshibatec-eu.co.uk

Portugal

Tel. +351 (0)214 222 064 comercial@toshibatec-eu.pt www.toshibatec-eu.pt

Tel. +34 (0)91 502 15 90 marketing@toshibatec-eu.es www.toshibatec-eu.es

Tel. +44 (0)870 890 7200 marketing@toshibatec-eu.co.uk www.toshibatec-eu.co.uk

GROUP Companies

TEC Italia, S.r.I. Gruppo Toshiba

Tel +39 (0)2 48 60 24 61 info@toshibatec.it

TEC Polska Sp. z.o.o. Tel. +48 (0)22 501 67 70 info@toshibatec-eu.pl www.toshibatec-eu.pl



B-SX4 & B-SX5



With over 20 years experience in producing barcode label printers the TOSHIBA B-SX4 & B-SX5 thermal transfer/direct thermal industrial printers provide world leading innovation and reliability. Built with the future in mind, the 'RFID Ready' B-SX printers take the barcode label printer to the next level. Ideal for use in all heavy-duty industries including chemicals, manufacturing, pharmaceuticals, textiles, electronics & telecom.

TOSHIBA

Leading Innovation >>>

The B-SX4 and B-SX5 combine ease-of-use with a very low total cost of ownership making them the ideal choice of flexible industrial printers.





POWER
ON LINE
ERROR

Speed

High-speed printing is of course the norm. But the overall throughput is enhanced by a fast 32 bit RISC CPU (SH-3 88 MHz), 8/16 MB DRAM image buffer, and 4 MB Flash Memory for programs and large data file storage.

Ease of use

Access to print head, platen, paper path and sensors is made quick and easy by the wide opening mechanism.





B-SX4 & B-SX5



Fast, reliable, easy and compatible at a lower total cost of ownership

A CD-ROM is provided with the printer that includes the Owners manual, technical manuals, BarTender UltraLite label printing software and Windows drivers - which all make the user's life easier.

High print quality

TOSHIBA's very own print heads - 203 dpi on the B-SX4 and 306 dpi on the B-SX5 - make these machines unique in the market. Innovations include high-precision heat history control in 7 stages, a new hyper heater mechanism and improved alpha protection layer.

The superb clarity is further enhanced by the new linear torque control of the TOSHIBA TEC double ribbon motor system. The on-the-fly ribbon save function allows ribbons to be saved without a detrimental effect on throughput (an option on the B-SX4). The TOSHIBA print heads also extend the print head life (100 km life time).

Reliability

A field-proven heavy-duty steel cabinet and a robust inner mechanism combine to ensure the incredible reliability of the B-SX4 and B-SX5. Several technological advances mean more performance and functionalities at a competitive price.

Full compatibility

Software and supplies are compatible with TOSHIBA TEC's previous models - the B-X printer range produced under the TEC brand.

Enhanced Features

Internet, E-mail, FTP, XML, RFID and BCI.

The enhanced functions offer many advantages including:

- remote printing and technical support
- less costly software integration thanks to standardised XML data exchange
- remote label format installation and updating (web print spooling)
- notification of errors and events
 data manipulation and processing
- data manipulation and processing using the BCI

Basic Command Interpreter

The BCI can run Basic programs allowing the manipulation of incoming print data to generate the correct label formats. This allows the printer to be connected to existing legacy systems eliminating the need for costly software changes. The BCI can also communicate with external devices allowing the easy integration of other technology systems.

Easy connectivity

The B-SX4/SX5 printers have an array of interface options:

Optional
Expansion I/O
USB v1.1 port
Built-in LAN board 10/100 Base
2-slots PCMCIA interface board
Wireless LAN 802.11b card
RFID Enabled

Suitable Applications

- Manufacturing
- Automotive
- Chemical Industry
- Pharmaceutical Industry
- Textile Industry
- Electronics
- Telecommunications
- Food Sector
- Retail Distribution
- Transport and Logistics
- Healthcare
- Utilities
- Government

RFID

RFID Technology satisfies the growing requirements of supply chain management. Data, text, barcodes and graphics can still be printed on labels in the usual way, but at the same time complementary information is stored on integrated circuits utilising radio frequency, ready for future reading or editing as required. In fact these printers treat the addition of RFID data as just another barcode. So for the user or programmer no knowledge of RFID is necessary. Just send the data as part of a label format and the printer does the rest.

HF 13.56 MHz

(only available in Europe)
The B-9704-H1-QP option enables the printer to encode chips at 13.56 MHz.
Current supported chips are C210,
C220, C240, C270 (I-Code), Tag-It,
ISO15693, and ISO18000 type 3.

UHF 869.5

The B-9704-U1-QP option enables the printer to encode chips at 869.5 MHz. Current supported chips are EPC Class0, Class0+, Class1, Class1 GEN2, and ISO-18000-6-B.

