



## **WPL206** | Light-Duty Desktop Label Printer **No-Nonsense Barcode Printer with Perfect Balance Between Price and Performance**



### **Key Features**

- High quality double-walled clamshell design
- 5 inches per second print speed
- 64 MB SDRAM and 128 MB Flash memory
- Easy media loading
- USB 2.0 standard
- WPL firmware for plug-n-play ease
- ENERGY STAR® qualified

# WPL206 | Light-Duty Desktop Label Printer

<b>RESOLUTION</b>	203 DPI (8 dots/mm)
<b>PRINTING METHOD</b>	Direct Thermal
<b>PRINT SPECS</b>	Max Print Speed: 5 IPS (127 mm per second) Max Print Width: 4.25 in (108 mm) Max Print Length: 90 in (2,286 mm) Max Label Capacity: 5 in OD (127 mm)
<b>PHYSICAL SPECS</b>	Dimensions: 6.77 in (W) x 6.50 in (H) x 7.68 in (D) / 172 mm (W) x 165 mm (H) x 195 mm (D) Weight: 2.87 lbs. (1.3 kg)
<b>PROCESSOR &amp; MEMORY</b>	32-bit RISC CPU; 128 MB Flash memory, 64 MB SDRAM
<b>INTERFACE</b>	USB 2.0
<b>POWER</b>	External universal switching power supply Input: AC 100-240V, 50-60Hz Output: DC 24V, 2.5A, 60W
<b>OPERATION</b>	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)
<b>SENSORS</b>	Transmissive gap sensor, Black mark reflective sensor, Head open sensor
<b>INTERNAL FONTS</b>	8 alpha-numeric bitmap fonts, Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font
<b>BARCODE</b>	1D Barcode: Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11, China Post; 2D Barcode: PDF-417, Maxicode, DataMatrix, QR code, Aztec, MicroPDF417
<b>FONT &amp; BARCODE ROTATION</b>	0, 90, 180, 270 degree
<b>PRINTER LANGUAGE</b>	WPL (Compatible to EPL, ZPL, ZPL II)
<b>MEDIA TYPE</b>	Continuous, black mark, fan-fold, notched (outside wound)
<b>MEDIA SPECS</b>	Width: 0.7 in ~ 4.5 in (19 mm ~ 114 mm) Thickness: 2.16 ~ 7.48 mil (0.055 mm ~ 0.19 mm) Core Diameter: 1 in ~ 1.5 in (25.4 mm ~ 38 mm) Label Length: 0.39 in ~ 90 in (10 mm ~ 2,286 mm)
<b>ENVIRONMENT</b>	Operation: 41 ~ 104°F, 25 ~ 85% non-condensing Storage: -40 ~ 140°F, 10 ~ 90% non-condensing
<b>SAFETY</b>	FCC Class A, CE Class A, C-Tick Class A, CB, CCC, ENERGY STAR®
<b>ENVIRONMENTAL CONCERN</b>	Comply with RoHS, WEEE
<b>INCLUDED</b>	Windows labeling software CD disk, Quick start guide, USB cable, Power cord
<b>WARRANTY</b>	2 Year Limited
<b>ACCESSORIES</b>	WPL206 Peel-off module, WPL206 Guillotine cutter - full cut or partial cut programmable, WPL206 Print head, 203DPI, KP-200 Plus keyboard display unit

