



Xi™ Series

High Performance Bar Code Printers

Higher Levels of Labeling

The newest family of five, *XiIIIPlus™* printers are superior performing *Xi*s! There's a labeling solution to fulfill any need—from 600dpi resolution for small label printing to an 8.5-inch print width for wide labels and forms. Exciting, new features include a 32-bit processor; increased memory for label formats, graphics, fonts and ZBI programs; and an early warning notification for printhead maintenance support. *XiIIIPlus* printers also offer more connectivity choices than their competitors, including ZebraLink, ZebraNet Wireless Card Socket; and USB 2.0, serial and parallel ports. *iSeries* (AS/400) network users choose from a wide range of Twinax/Coax and IPDS connectivity options. Add up all the bells and whistles, and it's easy to see why *XiIIIPlus* printers take high performance to an all-new level!

Everything you count on with Zebra's Xi Series printers, plus more!

Zebra's *Xi* Series is known for its high performance, mission-critical ruggedness. These hardworking printers are the ones to call on—24/7—in heavy duty, industrial operations.

XiIIIPlus printers from Zebra offer revolutionary features including:

- New 32-bit processor for faster throughput and processing speeds
- Increased 16MB SDRAM memory (over 12MB user available) for printing longer label formats
- 4MB non-volatile Flash memory (2MB user available)
- Early service warning notification for printhead maintenance support
- 300 unique darkness settings—great for printing on synthetic materials



Connect with it. Count on it.™

Xi Series™

Meet The *XIIIPlus*™ Family!

XIIIPlus printers offer superior connectivity solutions including:

▶ ZebraNet® Wireless Card Socket, which eliminates the costs of recabling when a printer is moved or reconfigured.

▶ ZebraLink™, a revolutionary real-time connectivity and control solution for Zebra printers, which includes:




1. Alert (with ZebraNet® PrintServer II)—enables a Zebra printer to send unsolicited status messages via email-enabled devices (e.g. pagers, cell phones, PCs and PDAs).
2. WebView (with ZebraNet PrintServer II)—enables the remote monitoring and configuration of Zebra printers using Web-based network tools.
3. ZBI™ (Zebra BASIC Interpreter)—programming language that works with ZPL II® to control and interpret incoming text and data.

ZebraLink gives you the freedom to create stand-alone applications using an *XIIIPlus* and peripheral devices without needing a PC host. ZBI can then transmit data captured by these devices over your LAN, WAN, or wireless network via e-mail or TCP/IP messaging.



Test drive an *XIIIPlus* with ZebraLink today at www.zebra.com/livelink!



90*XIIIPlus*™

The 90*XIIIPlus* printer is ideal for applications that require small, high-resolution bar code labels, such as tracking printed circuit boards and small parts, and identifying small products. The printer's standard 300dpi printhead ensures text, graphics and bar codes always print clearly—essential when label space is limited.

MAXIMUM PRINT AREA

Width: 3.4" /86mm

Length (with standard memory):
39" /991mm

RESOLUTION

300dpi/12dots per mm

MAXIMUM PRINT SPEED

8" /203mm per second

PHYSICAL CHARACTERISTICS

Width: 9.15" /232.4mm

Depth: 19.5" /495mm

Height: 15.5" /393.7mm

Weight: 50lbs./22.7kg

MEDIA SPECIFICATIONS

Label and liner width: .79" /20mm to
3.54" /90mm

Ribbon width: .79" /20mm to
3.4" /87mm



96*XIIIPlus*™

With a print resolution of 600dpi—the 96*XIIIPlus*—is unmatched at printing precise bar codes, text and graphics information in limited label space. This printer is ideal for applications that require extremely high resolution—labeling electronic components, telecommunication assemblies, computer peripherals, small pharmaceutical packaging, diagnostic research samples, and more.

MAXIMUM PRINT AREA

Width: 3.2" /81mm

Length (with standard memory):
20" /508mm

RESOLUTION

600dpi/23.5dots per mm

MAXIMUM PRINT SPEED

4" /102mm per second

PHYSICAL CHARACTERISTICS

Width: 9.15" /232.4mm

Depth: 19.5" /495mm

Height: 15.5" /393.7mm

Weight: 50lbs./22.7kg

MEDIA SPECIFICATIONS

Label and liner width: .79" /20mm to
3.54" /90mm

Ribbon width: .79" /20mm to
3.4" /87mm




HEADQUARTERS ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A.
PHONE: +1 847.634.6700 or +1 800.423.0442 FAX: +1 847.913.8766
WEB: www.zebra.com

OTHER LOCATIONS USA: California, Florida, Rhode Island, Wisconsin EUROPE: France, Germany, Italy, United Kingdom
ASIA-PACIFIC: Australia, China, Japan, Singapore, South Korea



An ISO 9001 registered company
©2002 ZIH Corp.
Printed in U.S.A.
#11211L, Rev. 4 (6/02) 20M

Xi Series™



140XiIIIPlus™

The 140XiIIIPlus gets the job done fast, printing at up to 12 inches per second (ips). With such powerful performance and steel construction, it is the ideal choice for high-volume, mission-critical applications with 24-hour duty cycles. The 140XiIIIPlus is also well suited for applications in which labels are required quickly, either on demand or in batches.

MAXIMUM PRINT AREA

Width: 5.04"/128mm

Length (with standard memory):
39"/991mm

RESOLUTION

203dpi/8dots per mm

MAXIMUM PRINT SPEED

12"/305mm per second

PHYSICAL CHARACTERISTICS

Width: 11.15"/283.2mm

Depth: 19.5"/495mm

Height: 15.5"/393.7mm

Weight: 55lbs./25kg

MEDIA SPECIFICATIONS

Label and liner width: 1.57"/40mm to
5.51"/140mm

Ribbon width: 1.57"/40mm to
5.1"/130mm

170XiIIIPlus™

The industrial-strength 170XiIIIPlus has a 12-gauge steel frame, 300dpi print resolution and the ability to print labels up to 6.6 inches wide at eight ips. Tough compliance labeling applications are no match for the 170XiIIIPlus, since it can easily print large numbers of AIAG, ODETTE, UCC/EAN-128 and other compliance labels on demand or in batches.

MAXIMUM PRINT AREA

Width: 6.6"/168mm

Length (with standard memory):
39"/991mm

RESOLUTION

300dpi/12dots per mm

MAXIMUM PRINT SPEED

8"/203mm per second

PHYSICAL CHARACTERISTICS

Width: 13.15"/334.4mm

Depth: 19.5"/495mm

Height: 15.5"/393.7mm

Weight: 67lbs./30.5kg

MEDIA SPECIFICATIONS

Label and liner width: 2"/51mm to
7.1"/180mm

Ribbon width: 2"/51mm to
6.7"/170mm

220XiIIIPlus™

The 220XiIIIPlus quickly prints labels up to 8.5 inches wide at 10ips. It is ideal for wide label applications such as printing chemical drum labels, primary metal standard labels, automotive industry labels, banner-sized labels and pallet and container shipping labels.

MAXIMUM PRINT AREA

Width: 8.5"/216mm

Length (with standard memory):
39"/991mm

RESOLUTION

203dpi/8dots per mm

MAXIMUM PRINT SPEED

10"/254mm per second

PHYSICAL CHARACTERISTICS

Width: 15.65"/397.5mm

Depth: 19.5"/495mm

Height: 15.5"/393.7mm

Weight: 72lbs./32.7kg

MEDIA SPECIFICATIONS

Label and liner width: 4.25"/108mm
to 8.8"/224mm

Ribbon width: 4.25"/108mm to
8.6"/220mm

For More Information

Contact your Zebra representative for additional printer specifications. For information on Zebra's other printers, supplies, software and accessories, ask your reseller, call +1 800.423.0442, or visit our Web site www.zebra.com.



Left
Standard media door
with clear panel

Right
Optional bi-fold media
door with clear panel

Xi Series™



Specifications at a Glance*

STANDARD FEATURES

Print methods: Thermal transfer or direct thermal
Construction: 12-gauge steel frame
ZebraLink™ connectivity
New processor for increased throughput and processing speeds
16MB SDRAM; 4MB non-volatile Flash memory
Advanced counters
Enhanced Alert notification—monitors printhead condition
300 unique darkness settings for print quality
USB 2.0 port for faster connectivity and throughput (plug and play)
Serial and parallel ports
Multilingual backlit LCD control panel
PCMCIA socket
Transmissive and reflective media sensors
Multi-level Element Energy Equalizer (E3) for superior print quality
Compact Flash (available August 2002)

Zebra Programming Languages

ZPL II®—Universal language for Zebra printers. Simplifies label formatting and enables format compatibility with other Zebra printers.
ZBI—Controls and interprets text and data from peripherals and non-ZPL printer programming languages. Transmits captured data over LAN, WAN, or wireless network via e-mail or TCP/IP messaging.

OPERATING CHARACTERISTICS

Environment

Operating Temp. (tt): 41°F/5°C to 104°F/40°C
Operating Temp. (dt): 32°F/0°C to 104°F/40°C
Storage/Transport Environ.: -40°F/-40°C to 140°F/60°C
Operating Humidity: 20–85% non-condensing
Storage Humidity: 5–85% non-condensing

Electrical

Universal power supply with power-factor correction 90–264 VAC; 48–62 Hz

Communication Interface Capabilities

USB 2.0 port (480M bits/second)
RS-232C/422/485 multi-drop
Hi-speed, bi-directional, IEEE 1284 parallel interface
ZebraNet® PrintServer II (optional)
ZebraNet Wireless Card Socket (optional)

Agency Approvals

Bi-National UL 60950 Third Edition/CSA CAN/CSA-C22.2 No. 60950-00 Third Edition; IEC 950/EN60950: 1992 w/amendments 1 through 4 (CB Scheme); EN55022: 1998 Class B; EN55024: 1998; EN61000-3-2, 3 w/amendment A12; Canadian ICES-003, Class B, FCC Class B; Argentina 92/98 Phase 3; Australia AS/NZS 3548; R.O.C. CNS 13438

MEDIA CHARACTERISTICS

Labels

Max. Roll Size: 8" /203mm O.D. on a 3" /76mm I.D. core
Thickness (label & liner): .003" / .076mm to .012" / .305mm
Media Types: Continuous, die-cut or black mark
For optimum print quality and printer performance, use Genuine Zebra Supplies.

Ribbons

Ribbon is recommended to be at least as wide as media.
Max. Roll Size: 3.2" /81.3mm O.D. on a 1" /25.4mm I.D. core
Standard Lengths: 1,476' /450m or 984' /300m; provides 3:1 & 2:1 media roll to ribbon ratios
Ribbon Setup: Ribbon wound ink side out

FONTS/GRAPHICS/SYMBOLOLOGIES

Fonts and Character Sets

Standard Fonts: 7 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
Sets: IBM® Code Page 850 International character set

Graphic Features

Supports user-defined fonts and graphics—including custom logos

Bar Code Symbolologies

Linear Bar Codes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case C Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digital extensions, Plessey, Postnet, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar, Planet Code
2-Dimensional: Codablock, PDF-417, Code 49, DataMatrix, Maxi Code, QR Code, Micro PDF-417, TLC 39

OPTIONS AND ACCESSORIES

ZebraNet PrintServer II
ZebraNet Wireless Card Socket
Rewind
Cutter (now available on all XiIIIPlus printers)
Bi-fold media door with clear panel
Label peel
Media supply spindle for 40mm cores (not available on 220XiIIIPlus)
Scalable and international fonts
PC cards
Applicator interface
IBM Twinax interface
IBM Coax interface
BAR-ONE® software
Compact Flash cards

*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.



HEADQUARTERS

ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A.
PHONE: +1 847.634.6700 or +1 800.423.0442 FAX: +1 847.913.8766
WEB: www.zebra.com

OTHER LOCATIONS

USA: California, Florida, Rhode Island, Wisconsin EUROPE: France, Germany, Italy, United Kingdom
ASIA-PACIFIC: Australia, China, Japan, Singapore, South Korea



An ISO 9001 registered company
©2002 ZIH Corp.
Printed in U.S.A.
#11211L, Rev. 4 (6/02) 20M



About BarcodesInc

Who We Are

BarcodesInc is North America's leading provider of... [The following text is intentionally obscured with noise for this block]

We Owe Our Success To You

Our success is due to the support of our customers... [The following text is intentionally obscured with noise for this block]

Why Choose BarcodesInc?

Dedicated Account A UbU Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same day.

Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service team.

Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BRANDS



AND MORE